

WORKSHOP TOOLS



Unsurpassed Heavy-Duty Performance

Blue-Point[®]



Welding Helmet, Auto Darkening

YA4603

Packing: 1

- Fixed shade auto darkening welding helmet has a lens that is designed for carbon arc welding processes. Two arc sensors provide a range of sensitivity to trigger the lens under most welding conditions.
- Fix delay
- Meets ANSI Z87.1-2003, CE, DIN 4647 PZ, EN379, EN175, CSA Z 94.3 and AS/NZS 1338.1 standards



| PART NO. | # OF SENSORS | SHADE | CLEAR SHADE | VIEWING AREA (Inches) | POWER |
|----------|--------------|-------|-------------|-----------------------|-------|
| YA4603 | 2 | #10 | #3 | 3.81 x 1.38 | Solar |

Floor Jack

Packing: 1

- Low Profile
- Dual hydraulic cylinders
- Soft rollers for smoother & silent operation
- Smooth lift of the vehicle
- Low profile allows usage on less space



| PART NO. | CAPACITY (tons) | MIN. HEIGHT (mm) | MAX. HEIGHT (mm) | DIMENSION (mm) | NET WEIGHT (kg) |
|----------|-----------------|------------------|------------------|-----------------|-----------------|
| YF2AP | 2 | 70 | 490 | 750 x 364 x 180 | 42 |
| YF3AP | 3 | 90 | 552 | 790 x 364 x 180 | 45 |

UV Leak Detection Flashlight Kit

ECFUVLITE

Packing: 1

- High intensity LED bulb with 100,000 hour service life
- Over four hours of peak performance per charge
- Power comparable to high intensity 75 watt lamps
- Compatible with all standard leak detection dyes
- Inspection range of up to 6'
- Includes (3) "AAA" batteries and fluorescence enhancing glasses



3 Ton Floor Jack



YF3PH

Packing: 1

- 3 Ton capacity
- Soft rollers for smoother and silent operation
- Smooth lift of the vehicle



| PART NO. | CAPACITY (tons) | MIN. HEIGHT (mm) | MAX. HEIGHT (inches) | SADDLE SIZE (mm) | FRAME LENGTH (mm) | HANDLE LENGTH (mm) |
|----------|-----------------|------------------|----------------------|------------------|-------------------|--------------------|
| YF3PH | 3 | 130 | 462 | 119 | 617 | 1,243 |





3 1/2 Ton Floor Jack

YA1707

Packing: 1

- Fast acting pump reaches lifting height in less than a pump to allow user to reach a variety of service height situations quickly
- One piece handle for professional users features a foam pad to limit damage to vehicles
- Universal joint release mechanism for smooth action
- Rolled side frames with generous flanges to resist flexing
- Low profile design allows for easy access under vehicles
- Floor Jack used to lift cars and light trucks
- Meets ANSI-PALD standards



| PART NO. | CAPACITY (tons) | MAX LIFT HEIGHT (inches) | LOW HEIGHT (inches) | SADDLE SIZE (inches) | FRAME LENGTH (inches) | HANDLE LENGTH (inches) | WEIGHT (lbs) |
|----------|-----------------|--------------------------|---------------------|----------------------|-----------------------|------------------------|--------------|
| YA1707 | 3 1/2 | 22 | 3 3/4 | 4 1/4 | 29 7/8 | 50 | 103 |

Motorcycle Floor Jack

YA1715

Packing: 1

- 1,500 pound capacity
- Low height of 4 1/2", maximum height of 14 3/4"
- Wide base for extra stability
- Double rubber lined pad provides extra protection to motorcycle while on the jack
- Pull handle assists user to maneuver jack into position
- One foot operation for ease of use
- Safety straps to secure motorcycle to jack
- Self locking safety feature and overload safety valve

