

Fully automatic station for recovering, recycling, and recharging R134a or HFO1234yf refrigerant



R134a

HFO1234yf

ECK3500-UP

ECK3500-HFO

ECK3900-UP

ECK3900-HFO

Type of refrigerant	R134a or HFO1234yf
Service procedure	Fully automatic or manual
Voltage	220-240V 50/60 Hz
Scale resolution	10 g
Oil scale resolution	5 g
Working temperature range	11/49°C
Filter system	1 filter for humidity (112 g)
Vacuum pump	100 litre/min capacity, 0.1 mbar vacuum level
Compressor	1/3 HP
Recovery speed	300 g/min in liquid phase
Refrigerant tank	22 litres, refillable (12 litres for HFO)
Hoses	3 metres
Dimensions/Weight cm.	55 x 60 x 105 kg 90
Dimensions/Weight Packaging cm.	70x70x122 kg.100
Thermal printer	Standard equipment
Pressure gauges	Class 1
Bottle heater	Standard equipment

**ECOTECHNICS®**



**Eck 3500-up**

**Eck 3500-HFO**



Italia

**Eck 3900-up**

**Eck 3900-HFO**



**5" Color Display** with icon messaging for easy use.



**Automatic HP-LP taps** with possibility to select from which port of the a/c system to recover /charge



**Nitro** Integrated Nitrogen and Nitrogen+Hydrogen leak detection with a connection for external tank



**Hybrid (patent pending)** Integrated function for service hoses flushing for use with vehicles equipped with electric compressors



**Hermetic containers,** for new oil and dye.

## ▲ STANDARD FEATURES

## ▼ OPTIONS

### FLUSHING KIT

For cleaning A/C systems by flushing with refrigerant.



### GAS IDENTIFIER

controlled by the machine.



### SANIFLUX

Passenger compartment air purification system.



### HERMETIC & REFILLABLE

containers, for new oils, and for dye (programmable).



### DIAG (only for R134a)

Dynamic diagnosis module.

