

## Fully automatic station for recovering, recycling, and recharging HFO<sub>1234yf</sub> refrigerant



HFO<sub>1234yf</sub>

ECK4000-HFO

ECK4000

Type of refrigerant	HFO <sub>1234yf</sub>
Service procedure	Fully automatic or manual
Voltage	220-240V 50/60 Hz
Scale resolution	10 g
Oil scale resolution	5 g
Working temperature range	11/49°C
Filter system	1 filter for humidity (112gr)
Vacuum pump	100 litre/min capacity, 0.1 mbar vacuum level
Sealed compressor	1/3 HP
Recovery speed	300 g/min in liquid phase
Refrigerant tank	12 litres refillable
Hoses	3 metres
Dimensions/Weight cm.	55 x 60 x 110 kg 90
Dimensions/Weight Packaging cm.	70x70x130 kg.100
Thermal printer	Standard
Pressure gauges	Class 1
Display	Graphic color touch screen
Bottle temperature sensor	Integrated
Bottle heater	Automatic

**ECOTECHNICS®**



**Eck 4000**

Special German OEM  
according to the VDA specifications



**Eck 4000-HFO**





**Large 7" Color Display** with touch-screen icon messaging for easy use.



**3 Hermetic & refillable** containers for new oils (PAG, POE) and for dye.



**Nitro** Integrated Nitrogen and Nitrogen+Hydrogen leak detection with a connection for external tank



**Hybrid (patent pending)** Flushing of station and service hoses for use with vehicles equipped with electric compressors.



**GAS IDENTIFIER** controlled by the machine (integrated) (ECK4000).

## ▲ STANDARD FEATURES

## ▼ OPTIONS

### FLUSHING KIT

For cleaning A/C systems by flushing with refrigerant.



### GAS IDENTIFIER

controlled by the machine (external) (ECK4000-HFO).



### SANIFLUX

Passenger compartment air purification system.

