

Impact Wrench



3/8" Impact Wrench, Compact

AT351

Packing: 1

- Built-in air inlet swivel
- 8 position power regulator
- Rotary action air motor is ball bearing mounted for balance, speed and power
- Ideal tool for small engine repair and bench work



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT351	3/8	237	9,700
BLOWS PER MINUTE	AIR CONSUMPTION, FREE SPEED (l/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)
1,200	71	1/4" - 18 NPT	3/8
VIBRATION LEVEL (m/s ²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
3.09	109.2	194	1.2

1/2" Impact Wrench

AT5500

Packing: 1

- Built-in five position adjustable air regulator plus a variable speed trigger for maximum user control
- Twin-hammer impact mechanism designed to hit hard yet offer tool longevity
- Inlet filter screens out dirt and grit; easy-to-remove filter for cleaning



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT5500	1/2	745	7,400
BLOWS PER MINUTE	AIR CONSUMPTION, FREE SPEED (l/min)	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s ²)
1,200	118.9	3/8	4
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (optional)
94	200	2.9	AT5500BOOT

1/2" Impact Wrench, Stubby

AT5500T

Packing: 1



- 550 ft-lb of torque, 9000 RPM and 1200 blows per minute
- Compact and lightweight for reduced user fatigue
- Twin-hammer impact mechanism hits harder and delivers increased tool longevity
- Polished aluminum housing is durable and easy to clean
- Ball-bearing mounted motor for smooth running operation
- Removable brass inlet filter protects tool from grit and debris
- Large forward/reverse lever for one-handed operation



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT5500T	1/2	745	9,000
BLOWS PER MINUTE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s ²)	SOUND LEVEL dBa PRESSURE
1,200	3/8	4	94
LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (optional)	
183	2.29	AT5500TBOOT	

1/2" Impact Wrench, Stubby Ext. Anvil

AT5500TL

Packing: 1



- 550 ft-lb of torque, 9000 RPM and 1200 blows per minute
- Compact and lightweight for reduced user fatigue
- Twin-hammer impact mechanism hits harder and delivers increased tool longevity
- Polished aluminum housing is durable and easy to clean
- Ball-bearing mounted motor for smooth running operation
- Removable brass inlet filter protects tool from grit and debris
- Large forward/reverse lever for one-handed operation
- Deep recessed application
- 2" anvil



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	
AT5500TL	1/2	745	
FREE SPEED (rpm)	BLOWS PER MINUTE	RECOMMENDED HOSE SIZE (inches)	
9,000	1,200	3/8	
VIBRATION LEVEL (m/s ²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
4	94	205	2.33