

# CR55 Aluminum Spotter

The CR55 is uniquely designed for aluminum repairs. Use on aluminum or steel to quickly attach studs for dent pulling, grounding, or accessories. The high tech discharge process creates the weld without damaging heat sensitive aluminum parts.

The power source is supplied complete with gun and 2-clamp earth cables. Standard supplies also include a set of threaded rivets specifically intended for aluminum application and threaded washers.



Maxilift dent puller

Item	Article No.	QTY
<b>Aluminum Spotter CR55</b> 115/220V 50-60Hz 1-ph	<b>33891</b>	
<b>Consisting of</b>		
Power source with 8.2 ft power cable (without plug), spot gun with 13' cable, 11.5' double earth cble with clamps, bag of 100 threaded rivets M4 x 15		
<b>Accessories for CR55</b>		
Maxilift Dent Puller with three hooks	33942	1
<b>Spare Parts for CR55</b>		
ALU M4x15 threaded rivets ALSI12 alloy	34019	100

## Technical Data

Input voltage	115V / 220V, 60 Hz, 1-ph (Auto Ranging)
Max installed power	1.6 Kw
Fuse rating (slow blow)	10A / 16A
Energy adjustment range	50 ÷ 1500 J
Number of welds per hour	1200/h
Protection class IP	23 c
Authorized for use in areas with increased hazard of electric shock	Yes
Weight	33 lbs (15 kg)
Dimensions	7" x 15" x 16" (176 x 370 x 401mm)

# CR35 Spotter



The CR35 is a sophisticated microprocessor controlled spotter for welding, dent pulling, and attaching studs, rivets, nuts, nails, and washers.



*The CR35 Start Kit contains all the basics for getting started*

Item	Article No.	Qty
<b>CR35 Start Kit</b>	<b>35139</b>	<b>1</b>
Electrode holder	34634	1
Carbon rod, 10 mm diameter	32322	2
Stud holder, 5 and 6 mm diameter	32318	1
Rivet holder, 3 and 5 mm diameter	32319	1
Stud, M6 x 20 (grounded)	31068	50
Stud, M5 x 18, coarse thread	31067	100
Clip rivets 3 x 4,5 mm	32506	100
Clip rivets 3 x 3,2 mm	31070	100
Crimped wire	32223	50
Contact tip	35474	1
Plastic box	35476	1
Wrench	35475	1
Wire electrode	35473	1

Item	Article No.	Qty.
<b>Spotter CR35 220V Single phase</b>	<b>33434</b>	<b>1</b>

#### Consisting of

Power source with 8.2 ft power cable, multi-function torch, ground cable, dent puller and Start Kit

#### Technical data

Input voltage	220 V, Single phase
Rated power at 50 %	2 kVA
Max power	16 kVA
Fuse rating (slow blow)	16A
Secondary no-load voltage	7V
Secondary short circuit current	2.8 kA
Duty cycle	5 %
Dimensions W x L x H	5 x 12 x 6 in
Weight	31 lbs (14 kg)

[www.car-o-liner.com](http://www.car-o-liner.com)



**CAR-O-LINER®**

*Your safety - our mission*

Car-O-Liner Company  
29900 Anthony Drive  
Wixom, MI 48393  
Tel: 1-248-624-5900  
Fax 1-248-624-9529  
[www.car-o-liner.com](http://www.car-o-liner.com)  
[info@car-o-liner.com](mailto:info@car-o-liner.com)

Distributor: